

IN THE CLAIMS:

Listing of claims:

B3

1. (currently amended) A method for adjusting the curvature of an air bearing surface of a slider, the slider including a leading edge, a trailing edge opposite the leading edge, and a back surface opposite the air bearing surface, the back surface including a substantially rectangular shape having four corner areas including first and second corner areas adjacent to the trailing edge and third and fourth corner areas adjacent to the leading edge, wherein the first and third corner areas are diagonally opposite to one another and the second and fourth corner areas are diagonally opposite to one another, the method comprising:

scribing at least one line in one of the first or second corner areas; ~~and~~

scribing at least one line in one of the third or fourth corner areas;

wherein the scribe lines are made in diagonally opposite corner areas; and

wherein the scribe lines are formed substantially perpendicular to the leading edge of the slider.

2. (original) A method as in claim 1, wherein the scribe lines in each of the diagonally opposite corner areas are substantially parallel to one another and to the leading edge.

3. (original) A method as in claim 2, wherein a plurality of scribe lines are made in one set of opposite corner areas selected from the group consisting of the first and third corner areas and the second and fourth corner areas.

4. (original) A method as in claim 1, wherein the scribe lines are made using a laser.

5. (original) A method as in claim 1, wherein the scribe lines are made using a system selected from the group consisting of pulsed laser, a continuous laser, and a diamond scribe.

6. (original) A method as in claim 1, wherein the scribe lines are made using a method that modifies the surface stress of the slider.

7. (original) A method as in claim 1, wherein at least one of said scribe lines is made up of a plurality of dots extending along a line.

8. (original) A method as in claim 1, wherein the scribe lines are formed to extend in a path selected from the group consisting of a straight path and a curved path.

9-13. (canceled)

14. (currently amended) A method for altering the twist of a slider including an air bearing surface, a leading edge, a trailing edge opposite the leading edge, and a back surface opposite the air bearing surface, the back surface including an upper right corner region and an upper left corner region adjacent to the trailing edge, and a lower right corner region and a lower left corner region adjacent to the leading edge, the method comprising:

forming a plurality of scribes in one of (i) the upper right corner region and the lower left corner region; or (ii) the upper left corner region and the lower right corner region, wherein the scribes are formed substantially perpendicular to the leading edge of the slider.

15. (original) A method as in claim 14, wherein the plurality of scribes are formed in the upper right corner region and the lower left corner region and the twist is increased.

16. (withdrawn) A method as in claim 14, wherein the plurality of scribes are formed in the upper left corner region and the lower right corner region and the twist is decreased.

17. (original) A method as in claim 14, wherein the scribes are formed as lines that are substantially parallel to one another.

18
19
20
21
22-23
24
25
26
27

18. (original) A method as in claim 14, wherein the scribe line formed closest to the trailing edge is located no less than 50 μm from the trailing edge.

19. (original) A method as in claim 14, wherein the scribes are formed using a laser.

20. (original) A method as in claim 14, wherein the scribes are formed using a system selected from the group consisting of pulsed laser, a continuous laser, and a diamond scribe.

21. (original) A method as in claim 14, wherein the scribes are made using a method that modifies the surface stress of the slider.

22-23. (canceled)

24. (original) A method as in claim 17, wherein the scribe lines are 250-300 μm in length.

25. (original) A method as in claim 17, wherein the scribe lines are 100-600 μm in length.

26. (original) A method as in claim 17, wherein adjacent laser scribe lines are separated from each other by up to 500 μm .

27. (currently amended) A method for altering the curvature of a slider including an air bearing surface, a leading edge, a trailing edge opposite the leading edge, and a back surface opposite the air bearing surface, the back surface including an upper right corner region, an upper middle region, and an upper left corner region adjacent to the trailing edge, the back surface also including a lower right corner region, a lower middle region, and a lower left corner region adjacent to the leading edge, the back surface also including a center right region, a center middle region, and a center left region, the method comprising:

63
Corr

forming a first scribe in one of the upper right corner region or the upper left corner region; and

forming a second scribe in one of the lower left corner region or the lower right corner region, wherein the first and second scribes are located in one of (i) the upper right corner region and lower left corner region, or (ii) the upper left corner region and lower right corner region;

wherein the scribes are formed perpendicular to the leading edge of the slider.

28. (withdrawn) A method as in claim 27, further comprising a step of forming a third scribe in at least one of the center right region, the center middle region, or the center left region.

29. (original) A method as in claim 27, wherein the scribes are formed using at least one of a pulsed laser, a continuous laser, a diamond scribe.

30. (original) A method as in claim 27, wherein the scribes are made using a method that modifies the surface stress of the slider.

31. (original) A method as in claim 27, wherein the scribe lines are made using a pulsed laser.

32-54. (canceled)

55. (currently amended) A method for altering the twist of a slider including an air bearing surface, a leading edge, a trailing edge opposite the leading edge, and a back surface opposite the air bearing surface, the back surface including an upper right corner region and an upper left corner region adjacent to the trailing edge, and a lower right corner region and a lower left corner region adjacent to the leading edge, the method comprising:

forming a first group scribes of scribes in one of (i) the upper right corner region and the lower left corner region; or (ii) the upper left corner region and the lower right corner region;

B3
Circled

measuring a twist value after forming the first group of scribes; and
forming a second group of scribes in one of (i) the upper right corner region and the lower left corner region; or (ii) the upper left corner region and the lower right corner region.

wherein the first group of scribes and the second group of scribes are formed perpendicular to the leading edge of the slider.

56. (previously presented) A method as in claim 55, wherein the first group of scribes are made in the upper right corner region and the lower left corner region to induce a positive change in twist, and the second group of scribes are made in the upper right corner region and the lower left corner region to induce a positive change in twist.

57. (previously presented) A method as in claim 55, wherein the first group of scribes are made in the upper right corner region and the lower left corner region to induce a positive change in twist, and the second group of scribes are made in the upper left corner region and the lower right corner region to induce a negative change in twist.

58. (withdrawn) A method as in claim 55, wherein the first group of scribes are made in the upper left corner region and the lower right corner region to induce a negative change in twist, and the second group of scribes are made in the upper left corner region and the lower right corner region to induce a negative change in twist.

59. (previously presented) A method as in claim 55, wherein the first group of scribes are made in the upper left corner region and the lower right corner region to induce a negative change in twist, and the second group of scribes are made in the upper right corner region and the lower left corner region to induce a positive change in twist.
